



#### **CLEAR 7 C**

Clear 7 C films help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Comply with European Standard EN 12600.



SOLAR SCREEN® Warranty 12 YEARS



Fire-resistance rating M1



Storage from -5°C to +40°C

**3 YEARS** 



European Standard EN 12600 1**B**1



REACH RoHS compliant

RESPECTED

# WIDTHS AVAILABLE:

122 cm

152 cm

#### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	5 %
Visible light transmission	85 %
Reflection of external visible light	11 %
Reflection of internal visible light	11 %
Total solar energy rejected	20 %
Total solar energy rejected 2*	21 %
Solar ratio:	
Solar energy reflection	10 %
Solar energy absorption	8 %
Solar energy transmission	82 %
Reduction in Solar Glare	15 %
g-value	0.83
u-value	5.7
Shading coefficient	0.9
Tensile strength (kg/cm <sup>2</sup> )	34
Elongation at break	125%
Installation type: Interior	
Roll length	30,5 m
Film composition	PET
Thickness	$210~\mu$

Colour from the outside:

TRANSPARENT

### **CONSTRUCTION**

- Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
  High optical quality polyester
- 3. Reinforced PS adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
- 4. Protection release liner, disposable after installation


#### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*\*

Clear single pane	<b>V</b>
Tinted single pane	<b>~</b>
Reflective tinted single pane	<b>~</b>
Clear double pane	<b>~</b>
Tinted double pane	<b>~</b>
Reflective tinted double pane	<b>~</b>
Gas-filled double pane - Low E	<b>~</b>
STADIP EXT. clear double pane	<b>~</b>
STADIP INT. clear double pane	<b>~</b>

recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m2.



## MAINTENANCE INSTRUCTIONS

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.