MAT ACID BUBBLE FREE

APPLICATIONS

Glass surface

Showcase

Advertising

Decoration

Urban advertising Exhibitions



FILMS PRINTING OPALESCENT



MAT ACID BUBBLE FREE

Mat Acid Bubble Free privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. Printable on any type of machine. Fast installation thanks to its bubblefree adhesive.



TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

| Ultraviolet transmission | > 25 % |
|---|--|
| Visible light | 45 % |
| transmission | |
| FRONT | |
| Technology | Polymeric PVC |
| Thickness | 80 µm |
| Finish | Opalescent White |
| COMPATIBILITY | |
| Surface(s) | Flat surface |
| Application type | Outdoor/indoor |
| Printing method | UV - UV gel - Aqueous |
| | print - Latex - Eco |
| | print - Latex - Eco |
| | solvent |
| DURABILITY | 1 |
| DURABILITY Outdoor resistance | 1 |
| | solvent |
| Outdoor resistance | solvent 8 years |
| Outdoor resistance Indoor resistance | solvent 8 years 10 years |
| Outdoor resistance Indoor resistance Anti-scratch/hard coat | solvent 8 years 10 years |
| Outdoor resistance Indoor resistance Anti-scratch/hard coat ADHESIVE | solvent 8 years 10 years No |
| Outdoor resistance Indoor resistance Anti-scratch/hard coat ADHESIVE Type | solvent 8 years 10 years No Acrylic solvent |
| Outdoor resistance Indoor resistance Anti-scratch/hard coat ADHESIVE Type | solvent 8 years 10 years No Acrylic solvent Bubble free/semi- |
| Outdoor resistance Indoor resistance Anti-scratch/hard coat ADHESIVE Type Performance | solvent 8 years 10 years No Acrylic solvent Bubble free/semi- |
| Outdoor resistance Indoor resistance Anti-scratch/hard coat ADHESIVE Type Performance LINER | solvent solvent 8 years 10 years No Acrylic solvent Bubble free/semi- permanent |

CONSTRUCTION

1. 80µ polymer PVC

PS adhesive, glass polymerization within 15 days
 Paper release liner allowing digital cutting



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.